

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23

APPLICATION

FOR UNITED STATES LETTERS PATENT

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT I, **Timothy R. Wilson**, a citizen of the United States,
have invented a new and useful railroad e-clip removal system of which the following
is a specification:

1
2
3 **Railroad E-Clip Removal System**
4
5

6 **CROSS REFERENCE TO RELATED APPLICATIONS**

7 Not applicable to this application.
8
9

10 **STATEMENT REGARDING FEDERALLY**
11 **SPONSORED RESEARCH OR DEVELOPMENT**

12 Not applicable to this application.
13
14

15 **BACKGROUND OF THE INVENTION**
16
17
18

19 **Field of the Invention**
20

21 The present invention relates generally to railroad e-clip removing devices and
22 more specifically it relates to a railroad e-clip removal system for efficiently and safely
23 removing railroad e-clips from a railroad track.
24
25

26 **Description of the Related Art**
27

28 Railroad clip members, such as e-clips, have been in use for years.
29 Conventional e-clips are slidably positioned within a tubular support member attached

1 to a rail pad as shown in Figure 1 of the drawings. E-clips are comprised of a resilient
2 metal that grip the rail under vibrating conditions without damage. Conventional
3 methods of removing e-clips are typically comprised of utilizing a hammer to drive the
4 e-clips from the tubular support member or elongate bar members utilized to pry the e-
5 clips from the tubular support member.

6
7 Conventional methods and tools for removing e-clips from a railroad track are
8 cumbersome. In addition, these methods and tools are not safe to remove e-clips
9 which are under significant stress and forces when securing a rail member thereby
10 causing them to "shoot outwardly" after being released from the tubular support
11 member. Also, it is time consuming to manually remove e-clips from the tubular
12 support member.

13
14 While these devices may be suitable for the particular purpose to which they
15 address, they are not as suitable for efficiently and safely removing railroad e-clips
16 from a railroad track. Conventional methods and tools for removing e-clips from
17 railroad tracks are difficult to utilize and inherently dangerous to the worker.

18
19 In these respects, the railroad e-clip removal system according to the present
20 invention substantially departs from the conventional concepts and designs of the prior
21 art, and in so doing provides an apparatus primarily developed for the purpose of
22 efficiently and safely removing railroad e-clips from a railroad track.

1

2 **BRIEF SUMMARY OF THE INVENTION**

3

4 In view of the foregoing disadvantages inherent in the known types of e-clip
5 removal devices now present in the prior art, the present invention provides a new
6 railroad e-clip removal system construction wherein the same can be utilized for
7 efficiently and safely removing railroad e-clips from a railroad track.

8

9 The general purpose of the present invention, which will be described
10 subsequently in greater detail, is to provide a new railroad e-clip removal system that
11 has many of the advantages of the railroad clip removal devices mentioned heretofore
12 and many novel features that result in a new railroad e-clip removal system which is
13 not anticipated, rendered obvious, suggested, or even implied by any of the prior art
14 railroad clip removal system, either alone or in any combination thereof.

15

16 To attain this, the present invention generally comprises an outer tube with an
17 outer cutout, an inner tube slidably positioned within a lumen of the outer tube, an
18 inner cutout within the inner tube having an engaging portion, and an actuator unit
19 attached to the tubes for extending/retracting the inner tube within the outer tube. The
20 engaging portion of the inert tube engages a portion of an e-clip when the actuator unit
21 is extended thereby forcing the e-clip from a tubular support member attached to a rail
22 pad. The e-clip is thereby safely and efficiently removed from the railroad track.

23

24 There has thus been outlined, rather broadly, the more important features of the
25 invention in order that the detailed description thereof may be better understood, and
26 in order that the present contribution to the art may be better appreciated. There are
27 additional features of the invention that will be described hereinafter and that will form
28 the subject matter of the claims appended hereto.

29

1 In this respect, before explaining at least one embodiment of the invention in
2 detail, it is to be understood that the invention is not limited in its application to the
3 details of construction and to the arrangements of the components set forth in the
4 following description or illustrated in the drawings. The invention is capable of other
5 embodiments and of being practiced and carried out in various ways. Also, it is to be
6 understood that the phraseology and terminology employed herein are for the purpose
7 of the description and should not be regarded as limiting.

8
9 A primary object of the present invention is to provide a railroad e-clip removal
10 system that will overcome the shortcomings of the prior art devices.

11
12 A second object is to provide a railroad e-clip removal system for efficiently
13 and safely removing railroad e-clips from a railroad track.

14
15 Another object is to provide a railroad e-clip removal system that does not
16 allow the e-clip to accidentally hit a worker.

17
18 An additional object is to provide a railroad e-clip removal system that
19 significantly reduces the amount of manual labor required to remove an e-clip.

20
21 Other objects and advantages of the present invention will become obvious to the
22 reader and it is intended that these objects and advantages are within the scope of the
23 present invention.

24
25 To the accomplishment of the above and related objects, this invention may be
26 embodied in the form illustrated in the accompanying drawings, attention being called
27 to the fact, however, that the drawings are illustrative only, and that changes may be
28 made in the specific construction illustrated and described within the scope of the
29 appended claims.

1
2 **BRIEF DESCRIPTION OF THE DRAWINGS**
3

4 Various other objects, features and attendant advantages of the present
5 invention will become fully appreciated as the same becomes better understood when
6 considered in conjunction with the accompanying drawings, in which like reference
7 characters designate the same or similar parts throughout the several views, and
8 wherein:
9

10 FIG. 1 is an upper perspective view of an e-clip attached to a tubular support
11 member for retaining a rail member of a railroad track.
12

13 FIG. 2 is an upper perspective view of the present invention.
14

15 FIG. 3 is a lower perspective view of the present invention.
16

17 FIG. 4 is a side view of the present invention with the inner tube retracted.
18

19 FIG. 5 is a side view of the present invention with the inner tube extended.
20

21 FIG. 6 is a cross sectional view taken along line 6-6 of Figure 5.
22

23 FIG. 7 is a cross sectional view taken along line 7-7 of Figure 5.
24

25 FIG. 8 is a bottom view of the present invention with the inner tube retracted.
26

27 FIG. 9 is a bottom view of the present invention with the inner tube extended.
28

1 FIG. 10 is an upper perspective view of the present invention positioned about
2 an e-clip to be removed.

3

4 FIG. 11 is a side view of the present invention positioned about an e-clip to be
5 removed.

6

DETAILED DESCRIPTION OF THE INVENTION

A. Overview

Turning now descriptively to the drawings, in which similar reference characters denote similar elements throughout the several views, FIGS. 1 through 11 illustrate a railroad e-clip removal system **10**, which comprises an outer tube **20** with an outer cutout **26**, an inner tube **30** slidably positioned within a lumen **24** of the outer tube **20**, an inner cutout **34** within the inner tube **30** having an engaging portion **32**, and an actuator unit **40** attached to the tubes for extending/retracting the inner tube **30** within the outer tube **20**. The engaging portion **32** of the inert tube engages a portion of an e-clip **18** when the actuator unit **40** is extended thereby forcing the e-clip **18** from a tubular support member **16** attached to a rail pad **14**. The e-clip **18** is thereby safely and efficiently removed from the railroad track.

B. Outer Tube

The outer tube **20** has an elongate structure with an outer cutout **26** as best shown in Figure 3 of the drawings. The outer tube **20** may have various cross sectional shapes such as rectangular, square, oval, circular and the like.

The outer tube **20** has an inner lumen **24** that slidably receives the inner tube **30** as shown in Figures 2 and 3 of the drawings. As shown in Figure 4 of the drawings, the outer tube **20** is preferably longer in length than the inner tube **30**. The outer tube **20** provides support and stability to the inner tube **30** when the engaging portion **32** of the inner tube **30** is engaging the e-clip **18**.

As shown in Figures 2 through 5 of the drawings, a plurality of legs **22** are attached to the outer tube **20**. The legs **22** are preferably on the outside portions of the outer tube **20** for providing support and stability to the outer tube **20** during usage.

1 One of the legs 22 is preferably engageable to a tubular support member 16 during
2 removal of an e-clip 18 (i.e. the leg that is positioned between the tubular support
3 member 16 and the rail member 12). In addition, one of the legs 22 is preferably
4 shorter than the other legs 22 and has a flanged portion for being positioned upon a rail
5 foot of a rail member 12 as shown in Figures 3 and 5 of the drawings.

6 7 **C. Support Structure**

8 As shown in Figures 4, 5, 10 and 11 of the drawings, a support structure 50
9 having is attached to the outer tube 20 for allowing the user to manipulate the present
10 invention. The support structure 50 preferably includes a handle member 52 attached
11 to the outer tube 20 as further shown in Figures 4, 5, 10 and 11. The support structure
12 50 may be comprised of various structures other than shown in the figures.

13 14 **D. Inner Tube**

15 The inner tube 30 is slidably positioned within the lumen 24 of the outer tube
16 20 as shown in Figures 3 through 5 of the drawings. The outer tube 20 and the outer
17 tube 20 preferably have a similar cross sectional shape, however the tubes 20, 30 may
18 have differing cross section shapes.

19
20 The inner tube 30 includes an inner cutout 34 and an engaging portion 32 as
21 further shown in Figure 3 of the drawings. The outer cutout 26 and the inner cutout 34
22 are preferably similar in position and size. The engaging portion 32 is engageable to
23 an e-clip 18 for forcing the e-clip 18 from the tubular support member 16 as shown in
24 Figure 11 of the drawings.

25
26 The engaging portion 32 is comprised of a lower rear edge of the inner cutout
27 34 as best illustrated in Figures 3, 8 and 9 of the drawings. The engaging portion 32 is
28 positioned near a rear portion of the outer cutout 26 when the inner tube 30 is retracted
29 as shown in Figure 4 of the drawings. The engaging portion 32 also preferably extends

1 below the outer cutout 26 for engaging the e-clip 18 as best shown in Figure 5 of the
2 drawings.

3
4 ***E. Actuator Unit***

5 The actuator unit 40 is attached to the outer tube 20 and includes an
6 extendable/retractable shaft member 42 as shown in Figures 3 through 9 of the
7 drawings. The actuator unit 40 may be comprised of any type of conventional actuator
8 such as but not limited to electrical actuator, hydraulic cylinder and the like. A control
9 switch is preferably attached to the support structure 50 for allowing the user to control
10 the actuator unit 40. If a hydraulic cylinder is utilized for the actuator unit 40, a
11 hydraulic fluid source is needed to operate the present invention.

12
13 The shaft member 42 is attached to the rear end of the inner tube 30 as shown
14 in Figures 6 and 7 of the drawings. The actuator unit 40 extends/retracts the inner tube
15 30 with respect to the outer tube 20 thereby allowing the engaging portion 32 to
16 engage the e-clip 18 during usage.

17
18 ***F. Operation of Invention***

19 In use, the user positions the present invention over the e-clip 18 to be removed
20 as shown in Figure 10 of the drawings. After the present invention is properly
21 positioned, the actuator unit 40 is thereafter extended thereby causing the engaging
22 portion 32 to engage the upper exposed portion of the e-clip 18 as shown in Figure 11
23 of the drawings. The engaging portion 32 continues to force the e-clip 18 outwardly
24 from the tubular support member 16 of the rail pad 14 as the toe portion of the e-clip
25 18 slides along the rail foot of the rail member 12. The actuator continues extending
26 until the e-clip 18 is fully removed from the tubular support member 16. The user then
27 simply lifts the present invention from the work area and is able to retrieve the
28 removed e-clip 18.

1 As to a further discussion of the manner of usage and operation of the present
2 invention, the same should be apparent from the above description. Accordingly, no
3 further discussion relating to the manner of usage and operation will be provided.
4

5 With respect to the above description then, it is to be realized that the optimum
6 dimensional relationships for the parts of the invention, to include variations in size,
7 materials, shape, form, function and manner of operation, assembly and use, are
8 deemed to be within the expertise of those skilled in the art, and all equivalent
9 structural variations and relationships to those illustrated in the drawings and
10 described in the specification are intended to be encompassed by the present invention.
11

12 Therefore, the foregoing is considered as illustrative only of the principles of
13 the invention. Further, since numerous modifications and changes will readily occur to
14 those skilled in the art, it is not desired to limit the invention to the exact construction
15 and operation shown and described, and accordingly, all suitable modifications and
16 equivalents may be resorted to, falling within the scope of the invention.